

ALMEMO® Measuring Instruments

ALMEMO® 2450-1L



**Compact ALMEMO®
measuring instrument
1 measuring input,
over 35 measuring ranges.
Runs in battery mode**

Technical data and functions

- Generously dimensioned 2-row segment display including units
- Easy and convenient to operate by means of 7 keys.
- Over 35 measuring ranges for
 - Thermocouple and NTC sensors
For the customer's own sensors ready-to-use ALMEMO® connectors are available. (see chapter 07)
 - Atmospheric humidity sensor, capacitive, dewpoint sensor, water detection probe, moisture in wood FHA636MF (see chapter 08)
 - Pressure transducer FDA602L/D, FD8214, FD8612, Tachometer, turbine flowmeter (see chapter 10)
 - Current clamps FEA604, Voltage / current measuring modules ZA990xAB (see chapter 11)
- Meteorological radiation probe heads FLA613 (see chapter 12)
- Carbon dioxide sensor FYAD00CO2, Carbon monoxide probe and ozone probe (see chapter 15),
- ALMEMO® plugs with multi-point adjustment are supported.
- Measuring functions
Measured value, zero-setting, saving of maximum / minimum values, hold function
- Test functions
Segment monitoring, range monitoring, sensor breakage indication, battery voltage check and display.

Technical data

Measuring input	1 ALMEMO® socket	Resolution	(see page 01.08 / 01.09)
Precision class	C (see page 01.06)	Linearization accuracy	(see page 01.08 / 01.09)
Measuring rate	2.5 mops	Sensor power supply	9 V, maximum 0.5 A
Measuring ranges (see 01.05 / 01.06)	NiCr-Ni(K), NiCroSil-NiSil(N), Fe-CuNi(L), Cu-CuNi(U), Cu-CuNi(T), PtRh10-Pt(S), Fe-CuNi(J), NTC Voltage Current Humidity, capacitive Dew point, mixture ratio, partial vapor pressure, enthalpy, rotating vanes, digital process (0 / 100 %), frequency, pulse, rotational speed, digital	Standard equipment LCD 7 segments 16 segments Keypad Power supply Battery set Current consumption Housing ABS (max. 70 °C) Environmental conditions and general technical data see page 01.04 onwards	Measured value 5 characters, 15 mm Function 4½ characters, 9 mm Units 2 characters, 9 mm 9 symbols 7 silicone keys 3 AA alkaline batteries approx. 10 mA without input modules 127 x 83 x 42 mm (LxWxH)

Accessories

Rubberized impact protection, gray	Order no. ZB2490GS2
DIN rail mounting	ZB2490HS
Magnetic fastening	ZB2490MH
Instrument case	ZB2490TK2

Standard delivery

Batteries, operating instructions, manufacturer's test certificate	Order no.
Compact measuring instrument ALMEMO® 2450-1L	MA24501L



幸託有限公司
XIN TOP CORPORATION

TEL : (02)2598-1199
FAX : (02)2596-2331

E-mail : info@xintop.com
Website : www.xintop.com