

ALMEMO® 2890-9



ALMEMO® precision measuring instrument with data logger function. Comprehensive range of functions for all application areas. Increased measuring accuracy, fast measuring rate. Generously dimensioned graphics display, bright illumination. 9 measuring inputs Runs on rechargeable batteries, charging via the device itself

Technical data and functions

- Increased measuring accuracy and stability
- Fast measuring rate, up to 50 measuring operations per second
With SD memory card, up to 100 mops, optional for 1 channel up to 500 mops
- 9 measuring inputs, electrically isolated
- Over 65 standard measuring ranges
- Support for ALMEMO® plugs with multi-point adjustment, special linearization, and special measuring ranges
- Option KL for independent multi-point adjustment or special linearization programmable in 30 points and management of calibration data saved in the sensor connector and the measuring instrument
- Higher measuring quality thanks to electrical isolation between measuring inputs and device power supply (device ground)
- Improved cold junction compensation with 2 sensors
- Data logger with internal EEPROM, sufficient for 100,000 measured values, configurable as linear or ring memory
- Memory connector with micro SD (accessory)
- Sleep mode for long-term recording
- Generously dimensioned graphics display, bright illumination, large display of measured values
- Measured values can be displayed graphically in line chart or bar chart form or numerically in various sizes.
- 3 user-defined menus can be freely configured from a range of 50 functions.
- Easy to operate by means of 4 soft-keys and cursor block, menu-guided with wizards and context-sensitive help windows
- Choice of languages : German, English, French
- 2 ALMEMO® output sockets, suitable for digital interfaces, analog output, trigger input, alarm contacts, memory card
- Runs on rechargeable batteries (as standard), high-speed charging in the device itself using mains unit, included in delivery

Technical data

Precision class	AA (see page 01.04)	Keypad	9 membrane keys (4 soft-keys), thumb-wheel
Measuring rate	(100), 50, 10 and 2.5 mops (measuring operations per second)	Memory, EEPROM	sufficient for 100,000 measured values
Measuring inputs	9 ALMEMO® input sockets	Date and time-of-day	Real-time clock, buffered with battery
Electrical isolation for analog sensors	with semiconductor relays (50 V) Additional electrical isolation between measuring inputs and power supply (device ground)	Power supply	Rechargeable battery pack 6 rechargeable NiMH batteries, 1600 mA Integrated high-speed charging (2.5 h)
Additional channels	4 function channels, device-internal	Mains adapter	ZB1112NA12 100 to 230 VAC to 12 VDC, 1.5 A electrically isolated
Sensor power supply	Rechargeable battery/ies 9 or 12 V, maximum 0.5 A Mains adapter 12 V, maximum 0.3 A	DC adapter cable	electrically isolated ZB2590-UK 10 to 30 V, 1 A
Outputs	2 ALMEMO® sockets, suitable for all output modules (analog / data / trigger / relay cables, memory, etc.)	Current consumption (without input and output modules)	Active mode approx. 37 mA With illumination approx. 45 to 100 mA Sleep mode approx. 0.05 mA
Standard equipment	Display	Housing	204 x 109 x 44 mm (LxWxH) ABS, 550g
Graphics display	128 x 128 pixels, 16 rows	Environmental conditions and general technical data	see page 01.04 onwards
Illumination	5 white LEDs, 3 brightness levels		

ALMEMO® 2890-9



Precision measuring instrument, 9 measuring inputs
Data logger with internal memory or external memory connector (accessory)

Accessories

Order no.

Memory connector with micro SD, including USB card reader (see chapter „General accessories“)
 DC adapter cable, 10 to 30 VDC, 12 V / 1 A, electrically isolated
 Generously dimensioned carry case, aluminum profile frame / ABS

ZA1904SD
 ZB2590UK
 ZB2590TK2

Connecting cables

Order no.

V24 data cable, electrically isolated
 Ethernet data cable, electrically isolated
 Analog output cable, electrically isolated , 1 x 20mA
 Analog output cable, electrically isolated , 2 x 10V
 Trigger and alarm cable (2 relays, 0.5 A, 50 V)
 Network technology, Bluetooth modules (see chapter „Networking“)

ZA1909DK5
 ZA1945DK
 ZA1601RI
 ZA1602RU
 ZA1006EKG

Options

Order no.

Multi-point adjustment, special linearization, management of calibration data
 Temperature ranges for 8 refrigerants
 Measuring rate 500 mops (SD card required)

OA2890KL
 SB0000R2
 SA0000Q5

Standard delivery

Order no.

Rechargeable battery pack, mains unit ZB1112NA12, USB data cable ZA1919DKU, case ZB2490TK2,
 Operating instructions, manufacturer's test certificate

Precision measuring instrument ALMEMO® 2890-9

MA28909

DAkkS or works calibration KE90xx, electrical, for measuring instrument (see chapter „Calibration certificates“).
 DAkkS calibration meets all the requirements regarding test resources laid down in DIN EN ISO/IEC 17025.

