

## PC CONFIGURATOR CABLE

(USB - miniature jack, isolated)

### Functions & Features

- Used to connect M-System Remote I/O or Signal Conditioners to the PC's USB port when setting parameters or monitoring operations of these devices on the PC Configurator Software

## MODEL: COP-US

### ORDERING INFORMATION

- Code number: COP-US

### PACKAGE INCLUDES...

- Driver software CD-ROM (1)

### GENERAL SPECIFICATIONS

#### Connection

**USB:** Type A connector

**Miniature Jack:** 3-pin, 2.5 mm dia.

**Housing material:** Resin (black)

**Isolation:** USB to miniature jack

### COMMUNICATION

**Communication protocol:** Full Speed USB2.0

(also usable with USB1.1 port)

**Transmission speed:** 38400 bps max.

### CONNECTED DEVICE

**USB:** PC/AT compatible

OS (Windows 7 (32-bit, 64-bit), Windows Vista (32-bit), Windows XP)

**Miniature jack side:** M-System Remote I/O, Signal Conditioners

### INSTALLATION

**Operating temperature:** -5 to +60°C (23 to 140°F)

**Operating humidity:** 30 to 90 %RH (non-condensing)

**Weight:** 75 g (2.6 oz)

### PERFORMANCE


**Insulation resistance:**  $\geq 100 \text{ M}\Omega$  with 500 V DC

**Dielectric strength:** 500 V AC @1 minute

(USB to miniature jack)



**DIMENSIONS unit: mm (inch)**



Specifications are subject to change without notice.

